



LG
Life's Good
(R22)



SINGLE SPLIT STANDARD

WALL MOUNTED TYPE (Cooling & Heating)

This can be easily installed in a small space and has exceptional cooling capacity. Designed for low-noise operation, it ensures a pleasant air conditioned environment. It also has Jet Cool for high level cooling and clean air supply through a Standard air purifying system.





SINGLE SPLIT STANDARD

HS-C0964GA0 / HS-C1264GA0 / HS-C1864GA0 / HS-C2665GA0
 HS-H0964GA0 / HS-H1264GA0 / HS-H1864GA0 / HS-H2665GA0

Indoor & Outdoor

FEATURES

- ≈Gold Fin Anti Corrosion™ ≈Jet Cool™ ≈Natural Wind by CHAOS Swing
- ≈Auto Restart ≈Wireless Remote Controller ≈Quiet Operation ≈Sleep Mode
- Auto Operation ≈7 hour OFF Setting Timer ≈One-Touch Air Filter (Anti-Bacteria)
- ≈Healthy Dehumidification.



Note: Due to our policy of innovation some specifications may be changed without notification

(R22)

INDOOR UNIT



		HS-C0964GA0		HS-C1264GA0		HS-C1865GA0		HS-C2665GA0		HS-H0964GA0		HS-H1264GA0		HS-H1865GA0		HS-H2665GA0		
Nominal Capacity (Rated)	Cooling	Btu/hr	9,000	12,000	18,500	26,000	9,000	12,000	18,500	26,000	9,000	12,000	18,500	26,000	9,000	12,000	18,500	26,000
		Kw	2,635	3,516	5,400	7,618	2,635	3,516	5,400	7,618	2,635	3,516	5,400	7,618	2,635	3,516	5,400	7,618
Running Current	Heating	Btu/hr	-	-	-	-	9,900	13,200	19,800	27,000	2,900	3,867	5,801	7,911	2,900	3,867	5,801	7,911
		Kw	-	-	-	-	4,2	6,0	9,2	12,6	4,2	6,0	9,2	12,6	4,2	6,0	9,2	12,6
Power Supply	Cooling	A	4.2	6.0	9.2	12.6	4.2	6.0	9.2	12.6	4.2	6.0	9.2	12.6	4.2	6.0	9.2	12.6
	Heating	A	4.0	4.8	8.4	12.6	4.0	4.8	8.4	12.6	4.0	4.8	8.4	12.6	4.0	4.8	8.4	12.6
Operational Temp. Range	Cooling	∅ / V / Hz	1 / 220 - 240 / 50	1 / 220 - 240 / 50	1 / 220 - 240 / 50	1 / 220 - 240 / 50	1 / 220 - 240 / 50	1 / 220 - 240 / 50	1 / 220 - 240 / 50	1 / 220 - 240 / 50	1 / 220 - 240 / 50	1 / 220 - 240 / 50	1 / 220 - 240 / 50	1 / 220 - 240 / 50	1 / 220 - 240 / 50	1 / 220 - 240 / 50	1 / 220 - 240 / 50	1 / 220 - 240 / 50
	Heating	°C	18 - 30	18 - 30	18 - 30	18 - 30	18	18	18	18	18	18	18	18	18	18	18	18
Air Circulation	Cooling	°C	-	-	-	-	30	30	30	30	30	30	30	30	30	30	30	30
	Heating	CMM / CFM	6.8 (240)	8.8 (311)	12.5 (442)	14.0 (495)	6.8 (240)	8.8 (311)	12.5 (442)	14.0 (495)	6.8 (240)	8.8 (311)	12.5 (442)	14.0 (495)	6.8 (240)	8.8 (311)	12.5 (442)	14.0 (495)
Sound Level (H / M / L)	Cooling	dB(A) ±3	32 / 29 / 24	37 / 33 / 30	40 / 37 / 30	46 / 43 / 39	32 / 29 / 24	37 / 33 / 30	40 / 37 / 30	46 / 43 / 39	32 / 29 / 24	37 / 33 / 30	40 / 37 / 30	46 / 43 / 39	32 / 29 / 24	37 / 33 / 30	40 / 37 / 30	46 / 43 / 39
	Heating	dB(A) ±3	33.1 x 10.6 x 6.1	33.1 x 10.6 x 6.1	42.9 x 11.8 x 7.1	42.9 x 11.8 x 7.1	33.1 x 10.6 x 6.1	33.1 x 10.6 x 6.1	42.9 x 11.8 x 7.1	42.9 x 11.8 x 7.1	33.1 x 10.6 x 6.1	33.1 x 10.6 x 6.1	42.9 x 11.8 x 7.1	42.9 x 11.8 x 7.1	33.1 x 10.6 x 6.1	33.1 x 10.6 x 6.1	42.9 x 11.8 x 7.1	42.9 x 11.8 x 7.1
Dehumidification Rate	Cooling	l/h	1.2 (2.56)	1.5 (3.20)	1.8 (3.83)	2.8 (5.95)	1.2 (2.56)	1.5 (3.20)	1.8 (3.83)	2.8 (5.95)	1.2 (2.56)	1.5 (3.20)	1.8 (3.83)	2.8 (5.95)	1.2 (2.56)	1.5 (3.20)	1.8 (3.83)	2.8 (5.95)
	Heating	l/h	1.2 (2.56)	1.5 (3.20)	1.8 (3.83)	2.8 (5.95)	1.2 (2.56)	1.5 (3.20)	1.8 (3.83)	2.8 (5.95)	1.2 (2.56)	1.5 (3.20)	1.8 (3.83)	2.8 (5.95)	1.2 (2.56)	1.5 (3.20)	1.8 (3.83)	2.8 (5.95)
Dimensions (W x H x D)	Body	mm	840 x 270 x 153	840 x 270 x 153	1090 x 300 x 180	1090 x 300 x 180	840 x 270 x 153	840 x 270 x 153	1090 x 300 x 180	1090 x 300 x 180	840 x 270 x 153	840 x 270 x 153	1090 x 300 x 180	1090 x 300 x 180	840 x 270 x 153	840 x 270 x 153	1090 x 300 x 180	1090 x 300 x 180
	Ind.Panel	mm	33.1 x 10.6 x 6.1	33.1 x 10.6 x 6.1	42.9 x 11.8 x 7.1	42.9 x 11.8 x 7.1	33.1 x 10.6 x 6.1	33.1 x 10.6 x 6.1	42.9 x 11.8 x 7.1	42.9 x 11.8 x 7.1	33.1 x 10.6 x 6.1	33.1 x 10.6 x 6.1	42.9 x 11.8 x 7.1	42.9 x 11.8 x 7.1	33.1 x 10.6 x 6.1	33.1 x 10.6 x 6.1	42.9 x 11.8 x 7.1	42.9 x 11.8 x 7.1
Weight	Body	kg	7	7	13.5	13.5	7	7	13.5	13.5	7	7	13.5	13.5	7	7	13.5	13.5
	Ind.Panel	mm	12.2	12.2	12.2	12.2	12.2	12.2	12.2	12.2	12.2	12.2	12.2	12.2	12.2	12.2	12.2	12.2
Piping Connections	Liquid	mm(inch)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)
	Gas	mm(inch)	9.52 (3/8)	12.7 (1/2)	12.7 (1/2)	15.88 (5/8)	9.52 (3/8)	12.7 (1/2)	12.7 (1/2)	15.88 (5/8)	9.52 (3/8)	12.7 (1/2)	12.7 (1/2)	15.88 (5/8)	9.52 (3/8)	12.7 (1/2)	12.7 (1/2)	15.88 (5/8)

OUTDOOR UNIT

		HS-C0964GA0/HS-H0964GA0		HS-C1264GA0/HS-H1264GA0		HS-C1865GA0/HS-H1865GA0		HS-C2665GA0/HS-H2665GA0		
Compressor	Capacity	Btu/hr	9,000	12,000	18,500	26,000	9,000	12,000	18,500	26,000
	Type		Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary
Refrigerant Charge	Charge	g	800	830	1170	1400	800	830	1170	1400
	Type		R22	R22	R22	R22	R22	R22	R22	R22
Fan Motor	Input / Output	W	63.2 / 25	63.2 / 25	145 / 74	145 / 74	63.2 / 25	63.2 / 25	145 / 74	145 / 74
	Type		AC Induction	AC Induction	AC Induction	AC Induction	AC Induction	AC Induction	AC Induction	AC Induction
Noise Level	Sound Press (1m)	dB(A) ±3	47	49	56	56	47	47	56	56
	Dimensions (W x H x D)	mm	770 x 245 x 540	770 x 245 x 540	870 x 655 x 320	870 x 655 x 320	770 x 245 x 540	770 x 245 x 540	870 x 655 x 320	870 x 655 x 320
Net Weight	Outdoor	kg	25	25	50	60	25	25	50	60
	Power Supply Cable (Includes earth)	No *mm ²	3 x 0.75	3 x 0.75	3 x 0.75	3 x 0.75	3 x 0.75	3 x 0.75	3 x 0.75	3 x 0.75
Blower Motor	Input / Output	W	27.6 / 7.8	34.3 / 15.1	50 / 19	58 / 25.6	27.6 / 7.8	27.6 / 7.8	50 / 19	58 / 25.6
	Elevation / Length	M	7 / 15	7 / 15	15 / 30	15 / 30	7 / 15	7 / 15	15 / 30	15 / 30
Drain Hose	mm	mm	26.5	26.5	26.5	26.5	26.5	26.5	26.5	26.5
	Running Current	Cooling / Heating	A	4.2 / 4.0	6.0 / 4.8	9.2 / 8.4	12.6 / 12.6	4.2 / 4.0	4.2 / 4.0	9.2 / 8.4
Air Circulation	Cooling	CMM / CFM	23 (812)	23 (812)	42 (1,483)	42 (1,483)	23 (812)	23 (812)	42 (1,483)	42 (1,483)
	Heating	CMM / CFM	23 (812)	23 (812)	42 (1,483)	42 (1,483)	23 (812)	23 (812)	42 (1,483)	42 (1,483)

LG Electronics South Africa (Pty) Ltd
 Rand Airport Road, Raceway Industrial Park, Monte Carlo Drive,
 Gosforth Park, Germiston, 1459
 P.O. Box 973, Alberton, South Africa, 1430
 Telephone number: 011 323 8000
 Website address: www.lgeaircon.com

Other Contacts

Johannesburg Toll Free: 0800 54 54 54
 Cape Town: 021 534 7950
 Durban: 031 716 5454



HS-H0964GA0



HS-H1264GA0



HS-H1865GA0



HS-H2665GA0