



LG
Life's Good
(R22)

WINDOW WALL

Window type units are not only stylish but compact with features, from the wireless remote controller, soft touch Electronic Controls and Gold Fin protection to the outdoor coil. All units are installed easily with most of models coming with slide-out Chassis and air flow can be controlled precisely by the 4-way Air Deflection system.






WINDOW WALL

W096BC / W126BC / W186BC / W246BC
W096BH / W126BH / W186BH / W246BH

FEATURES

- ≡ Gold Fin™ ≡ Anti Corrosion ≡ 4-Way Air Deflection
- ≡ One-Touch Air Filter ≡ Slide-Out Chassis



Note: Due to our policy of innovation some specifications may be changed without notification

(R22)

COOLING

| | | W096BC | | W126BC | | W186BC | | W246BC | |
|--------------------------|----------|------------|--------------------|--------------------|--------------------|--------------------|--|--------|--|
| Nominal Capacity (Rated) | Cooling | Btu/hr | 8,625 | 12,000 | 18,000 | 24,000 | | | |
| | | kw | 2.53 | 3.52 | 5.27 | 7.03 | | | |
| Running Current | Cooling | A | 4.4 | 5.3 | 9.2 | 12.8 | | | |
| | Heating | A | - | - | - | - | | | |
| Power Supply | | Ø / V / Hz | 1 / 220 - 240 / 50 | 1 / 220 - 240 / 50 | 1 / 220 - 240 / 50 | 1 / 220 - 240 / 50 | | | |
| Operational Temp. Range | Cooling | °C | 18 | 18 | 18 | 18 | | | |
| | Heating | °C | 30 | 30 | 30 | 30 | | | |
| Air Circulation | In / Out | CFM | 5.8 / 11.5 | 8.3 / 16.0 | 11.8 / 23.0 | 12.5 / 25.0 | | | |
| | In / Out | dB(A) ±3 | 48 / 54 | 51 / 57 | 58 / 66 | 58 / 66 | | | |
| Dehumidification Rate | | l/h | 1.0 | 1.3 | 1.9 | 2.2 | | | |
| Dimensions (W x H x D) | Body | mm | 469 x 353 x 525 | 600 x 380 x 555 | 660 x 428 x 770 | 660 x 428 x 770 | | | |
| Weight | Body | kg | 32 | 41 | 53 | 58 | | | |

HEATING & COOLING

| | | W096BH | | W126BH | | W186BH | | W246BH | |
|--------------------------|----------|------------|--------------------|--------------------|--------------------|--------------------|--|--------|--|
| Nominal Capacity (Rated) | Cooling | Btu/hr | 9,000 | 12,000 | 18,000 | 24,000 | | | |
| | | kw | 2.64 | 3.52 | 5.27 | 7.03 | | | |
| Running Current | Cooling | Btu/h | 9,000 | 12,000 | 18,000 | 24,000 | | | |
| | Heating | kw | 2.64 | 3.52 | 5.27 | 7.03 | | | |
| Power Supply | Cooling | A | 4.4 | 5.7 | 12.0 | 12.8 | | | |
| | Heating | A | 4.0 | 5.0 | 11.0 | 12.5 | | | |
| Power Supply | | Ø / V / Hz | 1 / 220 - 240 / 50 | 1 / 220 - 240 / 50 | 1 / 220 - 240 / 50 | 1 / 220 - 240 / 50 | | | |
| Operational Temp. Range | Cooling | °C | 18 | 18 | 18 | 18 | | | |
| | Heating | °C | 30 | 30 | 30 | 30 | | | |
| Air Circulation | In / Out | CFM | 7.0 / 12.0 | 8.4 / 16.0 | 11.2 / 22.0 | 12.5 | | | |
| | In / Out | dB(A) ±3 | 48 / 55 | 50 / 56 | 58 / 66 | 24.0 | | | |
| Dehumidification Rate | | l/h | 1.4 | 1.2 | 1.8 | 2.1 | | | |
| Dimensions (W x H x D) | Body | mm | 600 x 380 x 567 | 600 x 380 x 567 | 660 x 428 x 770 | 660 x 428 x 770 | | | |
| Weight | Body | kg | 39 | 46 | 58 | 60 | | | |

LG Electronics South Africa (Pty) Ltd
Rand Airport Road, Raceway Industrial Park, Monte Carlo Drive,
Gosforth Park, Germiston, 1459
P.O. Box 973, Alberton, South Africa, 1430
Telephone number: 011 323 8000
Website address: www.lgeaircon.com

Other Contacts

Johannesburg Toll Free: 0800 54 54 54
Cape Town: 021 534 7950
Durban: 031 716 5454



4-Way air Deflection



Auto Swing



Slide-out Chassis